

SAFETY DATA SHEET

Date Prepared : 12/14/2010
MSDS No : DT-400
Date Revised : 04/14/2015
Revision No : 5

Shop Floors

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Shop Floors
GENERAL USE: Cleaner
PRODUCT CODE: DT-400

DISTRIBUTOR

Truck Pro Inc
 1610 Century Center Parkway, Suite 107
 Memphis, TN 38134
Emergency Phone: (888)-782-5776

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (US Transportation) :(800) 424 - 9300

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Skin Corrosion, Category 1B
 Serious Eye Damage, Category 1

GHS LABEL



Corrosion

SIGNAL WORD: DANGER

HAZARD STATEMENTS

H314: Causes severe skin burns and eye damage.

PRECAUTIONARY STATEMENT(S)

Prevention:

P264: Wash hands thoroughly after handling.
 P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P301+P330+P331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
 P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P363: Wash contaminated clothing before reuse.
 P304+P340: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310: Immediately call a POISON CENTER or doctor/physician.

Storage:

P405: Store locked up.

Disposal:

P501: Dispose of contents/container in accordance with federal, state and local regulations.

SAFETY DATA SHEET

Date Prepared : 12/14/2010

MSDS No : DT-400

Date Revised : 04/14/2015

Revision No : 5

Shop Floors

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt. %	CAS
Water	to 100%	7732-18-5
2- Butoxyethanol	2 - 5%	111-76-2
Sodium Hydroxide	1 - 2%	1310-73-2
Sodium Polysilicate	1 - 2%	1344-09-8
Sodium Tripolyphosphate	1 - 2%	7758-29-4
Sodium Metasilicate	1 - 2%	6834-92-0

4. FIRST AID MEASURES

EYES: Flush eyes with water for at least 15 minutes. If pain and/or irritation persists, get medical attention.

SKIN: Flush affected area with water for 15 minutes. Remove contaminated clothing. If pain and/or irritation persists, get medical attention. Launder clothes before reusing.

INGESTION: Do not induce vomiting. Give 2 glasses of water. Get immediate medical attention.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

5. FIRE FIGHTING MEASURES

GENERAL HAZARD: None.

EXTINGUISHING MEDIA: Carbon dioxide, water, foam or dry chemical.

FIRE FIGHTING PROCEDURES: As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Contain spill. Absorb liquid and place in sealed container for disposal.

7. HANDLING AND STORAGE

STORAGE: Store in a tightly closed container.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

SAFETY DATA SHEET

Date Prepared : 12/14/2010

MSDS No : DT-400

Date Revised : 04/14/2015

Revision No : 5

Shop Floors

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
		EXPOSURE LIMITS					
		OSHA PEL		ACGIH TLV		Supplier OEL	
Chemical Name		ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
2- Butoxyethanol	TWA	50 ppm [1]	240 mg/m ³ [1]	20 ppm [2]	97 mg/m ³ [2]	NL ppm	NL ppm
	STEL	ppm	mg/m ³	ppm	mg/m ³	NL mg/m ³	NL mg/m ³
Sodium Hydroxide	TWA	[1]	2 [1]			NL	NL
	STEL	[3]	[3]			NL	NL

Footnotes:
 1. NL = Not Listed
 2. S = Skin
 3. C = Ceiling

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear safety glasses with side shields (or goggles).

SKIN: Wear rubber or nitrile gloves.

RESPIRATORY: None.

PROTECTIVE CLOTHING: None.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Butyl

COLOR: Purple

pH: > 12

FLASHPOINT AND METHOD: > (200°F) (Calculated)

FLAMMABLE LIMITS: N/D to N/D

VAPOR PRESSURE: Not Determined

VAPOR DENSITY: Not Determined

BOILING POINT: Not Determined

FREEZING POINT: Not Determined

SOLUBILITY IN WATER: Soluble

EVAPORATION RATE: Not Determined

SPECIFIC GRAVITY: 1.04

(VOC): < 5.000 %

10. STABILITY AND REACTIVITY

SAFETY DATA SHEET

Date Prepared : 12/14/2010
 MSDS No : DT-400
 Date Revised : 04/14/2015
 Revision No : 5

Shop Floors

HAZARDOUS POLYMERIZATION: Will not occur.

STABILITY: Stable.

CONDITIONS TO AVOID: None.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon.

INCOMPATIBLE MATERIALS: Strong acids, organic materials.

11. TOXICOLOGICAL INFORMATION

CARCINOGENICITY

Chemical Name	IARC Status
2- Butoxyethanol	3

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: Not available.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Corrosive Liquid N.O.S

TECHNICAL NAME: (Sodium Hydroxide)

PRIMARY HAZARD CLASS/DIVISION: 8

UN/NA NUMBER: 1760

PACKING GROUP: III

15. REGULATORY INFORMATION

UNITED STATES

DOT LABEL SYMBOL AND HAZARD CLASSIFICATION



Corrosive

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

FIRE: No **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** No

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

SAFETY DATA SHEET

Date Prepared : 12/14/2010
MSDS No : DT-400
Date Revised : 04/14/2015
Revision No : 5

Shop Floors

Chemical Name	Wt.%	CERCLA RQ
Sodium Hydroxide	1 - 2%	1,000 lbs.

16. OTHER INFORMATION


PREPARED BY: E. Spicer **Date Revised:** 04/14/2015

REVISION SUMMARY: This MSDS replaces the 04/14/2015 MSDS.

HMIS RATING

HEALTH	□	2
FLAMMABILITY	□	0
PHYSICAL HAZARD	□	0
PERSONAL PROTECTION	□	B

NFPA CODES



MANUFACTURER DISCLAIMER: The information provided in this Safety Data Sheet has been obtained from sources believed to be reliable. Manufacturer provides no warranties, either expressed or implied and assumes no responsibility for the accuracy or completeness of the data contained herein.