

DIRECTIONS:
DO NOT ALLOW PRODUCT TO DRY ON SURFACE.

Pressure Washing: Dilute 20:1 with water, adjusting dilution as needed. Allow to soak for 2-3 minutes, then rinse thoroughly with water.

Degreasing Engines and Machinery: Dilute 15:1 to 20:1 with water, adjusting dilution as needed. Allow to soak for 1-3 minutes, then rinse thoroughly with water.

Concrete Shop Floors: Dilute with 8 oz per gallon of water. Soak floor with solution, scrub if needed, remove solution with squeegee/wet vac, then rinse well.

Soak Cleaning: Mix 1 to 2 cups of EZ Degreaser per gallon of water in tank. (Tank may be heated to 180 degrees F if desired) Do NOT use with aluminum, galvanized steel or other non-ferrous metals.

EZ Degreaser

Heavy-Duty Cleaner & Degreaser with Butyl



WARNING
Causes skin irritation. Causes serious eye irritation. Wash hands thoroughly after handling. Wear protective gloves/eye protection.
IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs, get medical advice/attention. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

0 21855 07236 3

INGREDIENTS (CAS#): Water (7732-18-5),
2-Butoxyethanol (111-76-2), Sodium
Metasilicate (6834-92-0), Tallow Fatty Acid
(61790-12-3), Sodium Tripolyphosphate
(7758-29-4), Surfactants.

DANGER
KEEP OUT OF REACH OF CHILDREN
Net Contents: 1 gal (3.79 L)

Detco Industries, Inc.
Conway, AR
1-800-282-2133
www.detco.com

Detco