

Our Vision . . . a Safe Environment!!

DRY FILM

HIGH **TEMPERATURE ANTI-SEIZE** ANTI-FRICTION FILM

NET WT. 14 OZ. (396 Grams)

DANGER:

EXTREMELY FLAMMABLE HARMFUL OR FATAL IF SWALLOWED **VAPOR HARMFUL CONTENTS UNDER PRESSURE** SEE OTHER CAUTIONS ON BACK PANEL

TO REORDER CALL:

1-800-282-2133



MEETS MIL-A-907D

DRY FILM is an extreme range lubricant and anti-seize coating that withstands temperatures from -110°F to +1050°F. Resists pressures up to 100,000 psi. Inert to water, oil, alkalies and many acids. DRY FILM coating will not attract dirt or dust, DRY FILM contains pure Molybdenum Disulfide particles which burnish themselves into metal surfaces and provide a bonded lubricating film. DRY FILM provides lubrication even under salt spray conditions.

INDUSTRY USES: Foundries, automotive plants, vehicle maintenance, sewing trades, paper and corrugated converting, chemical plants, textile plants, woodworking, marine, agricultural and military equipment, road equipment, oil drilling equipment, aircraft maintenance, steel mills, mining operations, etc.

DIRECTIONS: Shake can vigorously before application. Surface must be free from all loose rust, oil, grease and old paint. Spray with a sweeping motion, holding can 8 to 10 inches away from surface. Apply a thin uniform coating. Allow to set approximately 3 to 5 minutes before applying second coat.

IMPORTANT: To prevent clogging: After each use, invert can and spray a few short bursts to clear valve.

DANGER: Contains Methylene Chloride (75-09-2), Toluene (108-88-3), Isopropyl Alcohol (67-63-0) and Liquefied Petroleum Gas (68476-85-7). Use only in a well ventilated area. Do not use near heat, sparks or open flame. Avoid contact with eyes or prolonged contact with skin. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F.

FIRST AID

IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

IF SKIN CONTACT: Wash with soap and water. If irritation persists, seek medical attention.

EXCESSIVE INHALATION: Remove to fresh air. Seek medical attention immediately. If breathing stops, give artificial

IF INGESTED: Do not induce vomiting. Seek medical attention immediately.

HMIS RATING: Health, 2; Flammability, 1; Reactivity, 1; Personal Protection, G.

> KEEP OUT OF REACH OF CHILDREN For further information consult Material Safety Data Sheet.



1375 Thomas G. Wilson Dr. **Conway, AR 72032** (800) 282-2133