

## DIRECTIONS:

**Truck Washing:** Dilute 32:1 with water. Spray product onto surface with low pressure, then rinse thoroughly with high pressure water. For brushless cleaning, at least 500 psi pressure is required for rinsing. Hold nozzle 12 inches from vehicle surface while rinsing.

**Bug Removal:** Dilute 25:1 with water. Spray onto surface and allow 1-3 minutes of contact time. Do NOT allow product to dry on surface. Proceed with normal truck washing procedure.

**2-Step Cleaning:** Lemon Truck Wash may be used as Step 2 in a 2-Step Cleaning process in combination with an acid product. Dilutions will vary between 32:1 and 64:1.

**Detco Industries, Inc.**  
Conway, AR  
1-800-282-2133  
[www.detco.com](http://www.detco.com)



# LEMON TRUCK WASH

## Non-Phosphate Truck Wash & Bug Remover

DANGER

KEEP OUT OF REACH OF CHILDREN  
Net Contents: 5 gal (18.93 L)

**Lemon Truck Wash** is a premium truck wash that removes diesel exhaust deposits, road film and bug residue from painted vehicle surfaces without time consuming brushing. It rinses easily and leaves no soap film residue when diluted properly.

### DANGER

Causes severe skin burns and eye damage.

Wash hands thoroughly after handling. Wear protective gloves/eye protection. **IF SWALLOWED:** Rinse mouth. Do NOT induce vomiting. **IF ON SKIN:** (or hair) Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. **IF INHALED:** Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store locked up. Dispose of contents/container in accordance with federal, state and local regulations.

**INGREDIENTS (CAS#):** Water (7732-18-5), 2-Butoxyethanol (111-76-2), Potassium Hydroxide (1310-58-3), Sodium Metasilicate (6834-92-0), Nonylphenol Ethoxylate (9016-45-9), Tetrasodium EDTA (64-02-8), Surfactants.



0992-005

