

DIRECTIONS:

Surface Preparation: If necessary, floor should be stripped free of old wax or finish. Scrub floor thoroughly with a good detergent or neutral cleaner such as Detco's **Kwik Mop**. Rinse well with clear water and allow to dry thoroughly.

Application Procedure: Apply a thin, even coat of sealer with a rayon mop or microfiber applicator. Allow at least 30 minutes of dry time. 2 to 3 coats are recommended for optimum performance. After sealer is dry, apply a floor finish such as Detco's **Magna Gloss 25**.

Typical coverage is 1,200 - 2,000 sq. ft. per gallon. Application rate will vary depending on surface and application method.

Note: Recommended for use with Detco floor care products.

Black Beauty II

Black Tile Floor Sealer

Restores Deep Black Color
Improves Adhesion of Floor Finish

CAUTION
KEEP OUT OF REACH OF CHILDREN
Net Contents: 5 gal (18.93 L)

Black Beauty II has been specially formulated to cover and seal old, scuffed, and worn asphalt and vinyl tiles often found in older postal facilities and office buildings.

When combined with Detco's **Magna Gloss 25**, the depth and luster of the gloss is greatly increased.

PROTECT FROM FREEZING

0103-005



CAUTION
KEEP OUT OF REACH OF CHILDREN
Dispose of contents/container in accordance with local/regional/national/international regulations.

INGREDIENTS (CAS#): Water (7732-18-5), Acrylic Polymers (Trade Secret), Diethylene Glycol Ethyl Ether (111-90-0), Carbon Black (1333-86-4) Tributoxo Ethyl Phosphate (78-51-3)


Detco Industries, Inc.
Conway, AR
1-800-282-2133
www.detco.com