

Sprays as an instant foaming, deep penetrating liquid that flows inside intricate chains and cables where the greatest stress occurs.

Provides a thick foam that clings to vertical surfaces. As foam breaks, lubricant penetrates into wire rope, rollers, pins, links and bushings of chains. Leaves a lubricating film, which reduces friction, wear and corrosion.

When applied to wire ropes and cables, the *Moly and other additives plate the strands to provide anti-wear and rust protection. (*Moly is molybdenum disulfide)

FOR USE ON: Chains, Wire Cable, Open Gears, Sprockets, Chain Saws, Drag Lines, Power Drives, Fittings, Booms, Road and Construction Machinery, Hoists, Winches, Cranes, Material Handling Equipment, Tow Lines, Linkages and Roller Assemblies.

USED BY: Industrial Facilities, Shipyards, Steel Mills, Aircraft Maintenance, Material Handling, Road Equipment, Construction, Mining, Containerized Shipping Companies.

Read all instructions before using this product.

DIRECTIONS: Shake well before using.

Make the can rattle 30 seconds before using. For proper spraying, can should be near room temperature (about 72°F / 22°C). Parts to be sprayed should be reasonably clean and dry. Spray, holding can 12 to 14 inches from point to be lubricated. Make sure arrow on spray tip points away. For point lubrication, use plastic extension tube, insert into nozzle – for reaching places where a spray pattern is not desired. Spray may be applied holding can upside down, sideways, right side up...in almost any position. If spray tip should close, remove and clean in solvent.

Cautions: May cause eye irritation. Prolonged or repeated contact may cause skin irritation. Inhalation of high concentrations or prolonged exposure can be irritating to eyes, nose and respiratory tract. May affect the following organs upon prolonged or repeated overexposure: liver, kidneys, nervous system. Keep away from heat, sparks, and flames. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F (49°C) as container may burst. Avoid prolonged exposure to sunlight. Use with adequate ventilation.

CONTAINS (CAS No.): Heavy Paraffinic Petroleum Distillate (64741-88-4), Dewaxed Heavy Paraffinic Distillate (64742-65-0), Mineral Spirits (8052-41-3), Coccoamide DEA (68603-42-9), and Propane (74-98-6).

FIRST AID:

EYES: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

IF SKIN: Wash with soap and water. If irritation persists seek medical attention.

INHALATION: Remove to fresh air. If symptoms develop, seek immediate medical attention. If not breathing, give artificial respiration.

INGESTION: In the unlikely event of swallowing: Call physician immediately. Do NOT induce vomiting unless directed by medical personnel. Never give anything by mouth to an unconscious person.

KEEP OUT OF REACH OF CHILDREN

For further information consult Material Safety Data Sheet.

HMS CODE:

0=MINIMAL 1=SLIGHT

2=MODERATE 3=SERIOUS 4=SEVERE

HEALTH	1
FLAMMABILITY	4
REACTIVITY	1
PERSONAL PROTECTION	X

DISTRIBUTED BY:

DETCO INDUSTRIES, INC.

P.O. BOX 430 CONWAY, ARKANSAS 72033

1-800-282-2133 or 1-501-329-6965

www.detco.com



CHAIN & CABLE

FOAMING CHAIN & CABLE LUBRICANT

- Protectant Fortified with *Moly
- Prevents Corrosion
- Deep Penetrating Action



Our Vision . . . a Safe Environment!!

DANGER:

HARMFUL OR FATAL IF SWALLOWED

FLAMMABLE

CONTENTS UNDER PRESSURE

SEE OTHER CAUTIONS ON BACK PANEL

NET WT. 15 OZ. (425 Grams)