

**DIRECTIONS:**

**NOTE:** This product may be harmful to some types of plastic. Always test in a small inconspicuous area first.

**Tar/Asphalt Removal:** Apply product to surface. Allow 1-5 minutes of contact time. Agitate if necessary, then rinse with water.

**Light-Duty Cleaning:** Dilute 1 part product with 9 parts water. Apply to surface and allow 1-5 minutes of contact time. Rinse thoroughly with water.

# ORANG-SOL 500

## Tar & Asphalt Remover

DANGER

KEEP OUT OF REACH OF CHILDREN  
Net Contents: 5 gal (18.93 L)



1251-C05



**DANGER**

Flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Very toxic to aquatic life with long lasting effects.

Keep away from heat/sparks/open flame/hot surfaces. - No smoking. Wear protective gloves/eye protection. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid breathing vapours/spray. Avoid release to the environment. IF ON SKIN: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical attention. Wash contaminated clothing before reuse. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER of doctor if you feel unwell. Collect spillage. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with federal, state and local regulations.

INGREDIENTS (CAS#): Petroleum Distillates (64742-47-8), D-Limonene (5989-27-5), 2-Butoxyethanol (111-76-2), Nonylphenol Ethoxylate (9016-45-9).



Detco Industries, Inc.  
Conway, AR  
1-800-282-2133  
www.detco.com