



**ULTRA BRITE** is a concentrated product formulated to clean and brighten aluminum. It reduces labor costs associated with trailer washing. It removes the heavy deposits of road film, diesel smoke and oxidation.

**DANGER**

May be corrosive to metals. Toxic if swallowed. Toxic in contact with skin. Causes severe skin burns and eye damage. May cause respiratory irritation. Keep only in original container. Wash hands thoroughly after handling. Avoid breathing mist/vapours. Use only outdoors or in a well ventilated area. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Absorb spillage to prevent material damage.

**FIRST AID**

**IF ON SKIN:** Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash with plenty of soap and water. Wash contaminated clothing before reuse. **IF SWALLOWED:** Rinse mouth. Do NOT induce vomiting. **INHALED:** Remove to fresh air and keep at rest in a position comfortable for breathing. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a **POISON CENTER** or doctor. Store locked up. Dispose of contents/container in accordance with federal, state and local regulations.



# ULTRA BRITE

## Concentrated Aluminum Brightener


**KEEP OUT OF REACH OF CHILDREN**

**ULTRA BRITE** will not streak or stain when used as directed. It can be used through spray and foam equipment fitted with an acid injector. It can also be used in a two step truck washing system along with **ULTRA WASH**.

**DIRECTIONS:  
READ ALL SAFETY PRECAUTIONS BEFORE USING THIS PRODUCT.**

Mix 1 cup of product with 1 gallon of water.(16:1) Dilution may vary depending on specific application.

1. Apply diluted solution to trailer starting from the bottom and moving to the top in small sections to avoid streaking.
  2. Allow **NO** more than 2 minutes of contact time. Do **NOT** allow solution to dry on the surface.
  3. Rinse starting at the top and moving to the bottom to avoid streaking.
- Brushing may be necessary to remove heavy diesel exhaust deposits.  
Do **NOT** apply this product to glass surfaces.



1810-4X1

**INGREDIENTS (CAS#):** Water (7732-18-5), Hydrochloric Acid (7647-01-0), Hydrofluoric Acid (7664-39-3), Nonylphenol Ethoxylate (9016-45-9), 2-Butoxyethanol (111-76-2), Ammonium Bifluoride (1341-49-7), Dye.

**NET CONTENTS:  
1 Gallon (3.79 L)**

**DANGER**  
See First Aid Statement on Side Panel

Detco Industries, Inc.  
Conway, AR  
1-800-282-2133  
www.detco.com