



ULTRA DEGREASER is a non-phosphate, heavy-duty, industrial strength cleaner and degreaser. It will remove grease, oil, dirt and other soils quickly and effectively.

DIRECTIONS:

DO NOT ALLOW PRODUCT TO DRY ON SURFACE.

Pressure Washing: Dilute 10:1 with water, adjusting dilution as needed. Allow to soak for 2-3 minutes, then rinse thoroughly with water.

Degreasing Engines and Machinery: Dilute 8:1 to 10:1 with water, adjusting dilution as needed. Allow to soak for 1-3 minutes, then rinse thoroughly with water.

Concrete Shop Floors: Dilute with 8 oz per gallon of water. Soak floor with solution, scrub if needed, remove solution with squeegee/wet vac, then rinse well.

Soak Cleaning: Mix 1 to 2 cups of **Detco 109** per gallon of water in tank. (Tank may be heated to 180 degrees F if desired) Do NOT use with aluminum, galvanized steel or other non-ferrous metals.

ULTRA DEGREASER

Heavy-Duty Degreaser

DANGER

Causes severe skin burns and eye damage. Wash hands thoroughly after handling. Wear protective gloves/eye protection.

FIRST AID

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. **IF ON SKIN:** Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. **IF INHALED:** Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a **POISON CENTER** or doctor. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store locked up. Dispose of contents/container in accordance with federal, state and local regulations.



KEEP OUT OF REACH OF CHILDREN

INGREDIENTS (CAS#): Water (7732-18-5), DBSA (68584-22-5), 2-Butoxyethanol (111-76-2), Sodium Hydroxide (1310-73-2), Surfactants, Dye.

NET CONTENTS:
1 Gallon (3.79 L)

DANGER
See First Aid Statement on Side Panel

Detco Industries, Inc.
Conway, AR
1-800-282-2133
www.detco.com



1814-4X1