

ANTI-LOCK is a copper-based anti-seize lubricant formulated to withstand high temperatures and extreme pressures. Continues ground conductivity better than ordinary lubricants. Seals out moisture, gases and corrosive fluids from threaded connections. Copper-Moly combo prevents seizing, galling and premature wear. Contains rust and corrosion inhibitors to assure long life of connectors. Synthetic oil-based formula.

USES: All threaded fittings including all nuts, bolts and screws, studs, pipes, plugs; hand and motor operated valves; gaskets, flanges and "O" rings; bushings, bearings, rollers and conveyors; gears, transmission boxes, chains and drives; electric motors, compressors, hoists, turbines and winches; furnaces, burner assemblies, regulators, pumps, valve stems, control chests and headers; man and inspection doors; cylinder head; fuel injectors, precombustion chambers, valve cages, turbo-charger fittings, guides and thread tubing; keyways and spark plugs; torque rod pins and tubes; air cylinder assemblies, pneumatic cylinder shafts, air slides and axle shafts.

DIRECTIONS: Shake can well before using. Clean surface thoroughly. Apply only enough to form a solid film over contact surfaces of threads, gaskets, bushings, etc. Assemble and wipe off excess.

MODO DE EMPLEO: Agite bien antes de usar. Limpie bien la superficie. Aplique solo lo necesario para formar una capa pequeña sobre la superficie de contacto de la rosca, juntas conexiones, etc. Ensamble y limpie el exceso.

DANGER: Extremely Flammable Aerosol. Contains gas under pressure; may explode if heated. Causes eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear eye protection. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. Avoid breathing mist, vapors or spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. Store in a well-ventilated place. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Dispose of contents and container in accordance with local, state, and national regulations.

PELIGRO: Aerosol extremadamente inflamable. Contiene gas a presión; puede explotar si se calienta. Provoca irritación ocular. Puede causar somnolencia o mareos. Puede ser mortal en caso de ingestión y penetración en las vías respiratorias. Mantener alejado del calor, chispas, llamas abiertas y superficies calientes. -No fumar. No rocíe sobre una llama abierta u otra fuente de ignición. Recipiente a presión: No perforar ni quemar, incluso después de su uso. Protéjase de la luz solar. No lo exponga a temperaturas superiores a 50°C / 122°F. Almacenar en un lugar bien ventilado. Lávese bien las manos después de manipular. Use protección para los ojos. Si entra en contacto con los ojos: Enjuague cuidadosamente con agua durante varios minutos. Quite las lentes de contacto, si lleva y es fácil de hacer. Continúe enjuagando. Si la irritación ocular persiste: busque atención o consejo médico. Evite respirar neblina, vapores o aerosoles. Úselo solo al aire libre o en un área bien ventilada. En caso de inhalación: lleve a la persona al aire libre y manténgala cómoda para respirar. Llame a un centro de intoxicaciones o un médico si no se siente bien. Almacenar en un lugar bien ventilado. En caso de ingestión: Llame inmediatamente a un centro de toxicología o un médico. No induzca el vomito. Deseche el contenido y el recipiente de acuerdo con las regulaciones locales, estatales y nacionales.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.



ADVERTENCIA: Cáncer y daños reproductivos: www.P65Warnings.ca.gov.

CONTAINS (CAS#): Polybutene (9003-29-6), Heptane (142-82-5), Copper (7440-50-8), Acetone (67-64-1), Propane/n-Butane (68476-86-8).

HMIS Ratings: Health 1, Flammability 3, Reactivity 1, Protection 3.

Made in USA



DISTRIBUTED BY:



TO REORDER CALL:

1-800-282-2133

PO BOX 430 CONWAY, AR 72033 • 1-800-282-2133 or 1-501-329-6965



ANTI-LOCK

COPPER-BASED ANTI-SEIZE

ANTI AGARROTAMIENTO A BASE DE COBRE



Reduces Seizing

Temperature Range -60°F to +1800°F

Imbedded with Copper to Improve Conductivity

50 State VOC Compliant

ANGER/PELIGRO:

EXTREMELY FLAMMABLE AEROSOL. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. AEROSOL EXTREMADAMENTE INFLAMABLE. CONTIENE GAS A PRESIÓN; PUEDE EXPLOTAR SI SE CALIENTA.

NET WT. 12 OZ. (340 g)