

Date issued: 06/06/2025

SDS number: 0056

Anti-Lock

1. Identification

Product code: 0056

Product identifier: Anti-Lock
Relevant identified uses: Lubricant

Manufacturer / Supplier

Detco Industries, Inc.

PO Box 430

Conway, AR 72033

Customer Service: 800-282-2133 E-Mail: support@detco.com Web: www.detco.com

Emergency telephone number (24 hour)

Poison Control Center (Medical) : (877) 800-5553 **CHEMTREC (US Transportation) :** (800) 424-9300

2. Hazard identification

Classification of the substance or mixture

Health hazards:

Eye Irritation, Category 2A Skin Irritation, Category 2 Target Organ Toxicity (Single exposure), Category 3 Aspiration Hazard, Category 1

Physical hazards:

Liquefied Gases Flammable Aerosols, Category 1

Label elements



Exclamation mark



Flame



Gas cylinder



Health hazard

Signal word: DANGER
Hazard statement(s)

H222: Extremely flammable aerosol.

H280: Contains gas under pressure; may explode if heated.

H320: Causes eye irritation.

H336: May cause drowsiness or dizziness.

H304: May be fatal if swallowed and enters airways.

Precautionary statement(s)

Prevention:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P264: Wash hands thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P271: Use only outdoors or in a well-ventilated area.



Date issued: 06/06/2025

SDS number: 0056

Anti-Lock

Response:

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P314: Get medical advice/attention if you feel unwell.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor/...

P331: Do NOT induce vomiting.

Storage:

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P403: Store in a well-ventilated place.

Disposal:

P501: Dispose of contents/container in accordance with federal, state, and local regulations.

3. Composition/information on ingredients

Chemical name	% w/w	CAS No.
N-butane	20 - 30	106-97-8
Acetone	10 - 20	67-64-1
Propane	5 - 15	74-98-6
N-heptane	5 - 10	142-82-5
Distillates, Petroleum, Hydrotreated Light	5 - 10	64742-47-8

4. First-aid measures

Eye: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

Skin: Wash with soap and water. Get medical attention if irritation develops or persists.

Ingestion: Get immediate medical attention. Do not induce vomiting unless instructed to do so by poison center or physician.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Most important symptoms and effects, both acute and delayed

Acute effects: Prolonged contact with skin may cause irritation. Causes eye irritation including redness, tearing, and pain. Inhalation of vapors may cause nausea, dizziness, and drowsiness. Ingestion may cause gastointestinal irritation, nausea, vomiting, and diarrhea. Small amounts of liquid aspirated into lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary edema.

Chronic effects: Dermatitis may occur due to long-term irritation. May cause liver and kidney damage.

Indication of immediate medical attention and special treatment needed, if necessary: Treat symptomatically.

5. Fire-fighting measures

General hazard: None known.

Suitable extinguishing media: Carbon dioxide, water, foam or dry chemical.

Fire fighting equipment: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Sensitivity to static discharge: None Sensitivity to mechanical impact: None



Date issued: 06/06/2025 SDS number: 0056

Anti-Lock

Hazardous decomposition products: Oxides of carbon

6. Accidental release measures

Small spill: Remove all sources of ignition. Contain spill. Absorb liquid and place in a sealed container for disposal. Avoid runoff into storm sewers and ditches which lead to waterways.

7. Handling and storage

General procedures: Store as Level 3 Aerosol (NFPA 30B)

Precautions for safe handling: Follow all SDS/label precautions even after container is emptied because it may retain product residues.

Conditions for safe storage: Protect from sunlight. Store in a well ventilated place. Do not expose to temperatures exceeding 50C/122F. Do not pierce or burn, even after use.

8. Exposure controls/personal protection

Exposure controls

Control parameters							
		Occupational exposure limit values					
Chemical name	Ту	Туре		mg/m³			
Acetone	OSHA PEL	TWA	1000	2400			
	ACCILI TI V	TWA	500				
	ACGIH TLV	STEL	750				
	Complian OF	TWA	NL	NL			
	Supplier OEL	STEL	NL	NL			

Appropriate engineering controls: Showers, eyewash stations and ventilation systems.

Individual protection measures, such as personal protective equipment

Eye / face protection: Safety glasses with side shields (or goggles).

Skin protection - hand protection: Rubber or nitrile gloves.

Respiratory protection: None needed with adequate ventilation.

Skin protection - other: No special technical protective measures are necessary. Wear protective clothing if needed.

Occupational hygiene practices: Handle in accordance with good industrial hygiene and safety practices.

9. Physical and chemical properties

Physical state: Aerosol

Color: Copper Odor: Solvent

pH: Not yet determined

Flash point: Not yet determined

Evaporation rate (n-butyl acetate = 1): Not yet determined

Flammability: Extremely Flammable Aerosol

Explosion limit / flammability limit notes: Not yet determined



Date issued: 06/06/2025

SDS number: 0056

Anti-Lock

Vapor pressure: Not yet determined

Relative vapor density: Not yet determined

Relative density: 0.87 to 0.89 g/mL

Solubility: Miscible

Partition coefficient n-octanol/water (logarithmic value): Not yet determined

Auto-ignition temperature: Not yet determined

VOC content: 39.82 %

10. Stability and reactivity

Reactivity: Certain plastics, rubber, and coatings **Dangerous polymerization:** Will not occur.

Chemical stability: Stable

Conditions to avoid: Temperatures above 120F, heat, flame and sources of ignition.

Possibility of hazardous reactions: None known.

Hazardous decomposition products: Oxides of carbon.

Incompatible materials: Strong oxidizers, strong alkali, chemically active metals, concentrated nitric acid

11. Toxicological information

Skin corrosion / irritation: No data available.

Serious eye damage / irritation: No data available.

Respiratory or skin sensitization: No data available.

Germ cell mutagenicity: No data available.

Carcinogenicity

Notes: No data available.

Reproductive toxicity: No data available.

Specific Target Organ Toxicity - single exposure: No data available.

Specific Target Organ Toxicity - repeated exposure: No data available.

Aspiration hazard: No data available.

12. Ecological information

Ecotoxicological information: No data available.

Bioaccumulative potential: Components in this product can bioaccumulate in aquatic organisms.

Environmental data: No data available.

13. Disposal considerations

Disposal methods: Dispose of in accordance with federal, state and local regulations.

Empty container: Do not reuse container.

14. Transport information

USA Department of Transport Regulations (DOT)

UN proper shipping name: Aerosols, Ltd. Qty

UN number: UN1950



Date issued: 06/06/2025

SDS number: 0056

Anti-Lock

Transport hazard class(es): 2.1 Packing group, if applicable: N/A

15. Regulatory information

UNITED STATES

CERCLA Hazardous Substances and Reportable Quantities (RQ)

Chemical name	% w/w	CERCLA rq
Acetone	10 - 20	5,000

TSCA (The Toxic Substances Control Act)

Chemical name	CAS No.
N-butane	106-97-8
Acetone	67-64-1
Propane	74-98-6
N-heptane	142-82-5
Distillates, Petroleum, Hydrotreated Light	64742-47-8


CAA 112(b) Hazardous Air Pollutants

Chemical name	% w/w	CAS No.
N-butane	20 - 30	106-97-8
Propane	5 - 15	74-98-6

16. Other information

Prepared by: E. Spicer Date Prepared: 06/06/2025

HMIS rating Health 1 Flammability 3 Physical hazard 1 Personal protection B



Manufacturer disclaimer: The information provided in this Safety Data Sheet has been obtained from sources believed to be reliable. Manufacturer provides no warranties, either expressed or implied and assumes no responsibility for the accuracy or completeness of the data contained herein.